

Model		P250WJD		P260/HP220WYM	
				Low Pressure	High Pressure
Compressor Rotary Screw / Single-Stage	Free-Air Delivery – cfm (m <sup>3</sup> /min)	250 (7.1)		260 (7.4)	220 (6.2)
	Rated Operating Pressure – psig (bar)	100 (7.0)		100 (7.0)	150 (10.3)
	Pressure Range – psig (bar)	80 – 125 (5.5 – 8.6)		80 – 125 (5.5 – 8.6)	80 – 175 (5.5 – 12.1)
	Air Discharge Outlet NPT Size – in (mm)	0.75 (19.0)		0.75 (19.0)	
	Air Discharge Outlet Quantity	2		2	
	Fuel Tank Capacity – gal (L)	27 (102)		29 (110)	
Engine	Make/Model	John Deere/4045T		Yanmar/4TNV98T	
	Emission Tier Level	Tier 3		Tier 3	
	Number of Cylinders	4		4	
	Displacement – cu in (L)	275 (4.5)		203 (3.3)	
	Rated Speed – rpm	2300		2500	2150
	Idle Speed – rpm	1500		1600	
	Bhp @ Rated Speed (kW)	75 (55.9)		79 (59)	
	Electrical – volts	12		12	
	Hours of Operation @ Full Load	6.9		7.8	NA
Dimensions w/ Running Gear	Length – in (mm)	137.6 (3494)		137.6 (3494)	
	Width – in (mm)	68.5 (1740)		68.5 (1740)	
	Height – in (mm); Including lifting bail	66 (1676)		66 (1676)	
	Track Width – in (mm)	59 (1499)		59 (1499)	
	Tire Size – in	15		15	
	Shipping Weight – No Fuel – lb (kg)	2820 (1279)		2427 (1101)	
	Working Weight – w/ Fuel – lb (kg)	3027 (1373)		2638 (1196)	
	Length – in (mm)	88 (2235)		88 (2235)	
Dimensions w/o Running Gear	Width – in (mm)	49.3 (1252)		49.3 (1252)	
	Height – in (mm); Including lifting bail, tailpipe and mtg pedestal	58 (1473)		58 (1473)	
	Shipping Weight – No Fuel – lb (kg)	2595 (1177)		2202 (999)	
	Working Weight – w/ Fuel – lb (kg)	2802 (1271)		2414 (1095)	

#### Available Options (factory installed)

- 1,000 CCA battery
- 2" or 2-5/16" ball hitch
- 4-in-1 combo gauge for volt meter, engine oil pressure, engine oil coolant and discharge air temperature
- 7 kW onboard generator with three 120-volt duplex receptacles (only available on P260/HP220WYM)
- 85" drawbar
- Additional service outlets
- Amber roof light, revolving or strobe
- Block heater
- Central drains
- Cold-weather starting aid; less ether container
- Electric or hydraulic brakes (electric brakes standard on P250WJD and P260/HP220WYM)
- Fuel level gauge
- Fuel tank strainer
- Full diagnostic panel
- Hose reel with 100' capacity for 3/4" (19 mm) ID hose, single or double reel with OSHA valve(s)
- Inline oilers for tool lubrication
- Key lock doors or ignition
- Lighted control panel
- Mechanical air filter maintenance indicator
- Padfoot instead of caster wheel
- Rear bumper
- Rear drop leg (requires optional rear bumper)
- Spark arrestor or rain cap
- Tachometer